




## 2 Rollers

series

### Self cleaning



#### 2.6.4 - Return rollers with helical steel cage for self cleaning

Used in the return section to support the belt when the conveyed material is very adhesive, as with for example clay.

They may be positioned on any part of the conveyor return section, when it is relatively short.

When these rollers are produced with a spiral steel cage, it is attached to the two end caps with similar characteristics to the PSV rollers series.

The spiral cage, in permanent contact with the dirty side of the belt, removes material from the belt using its natural rotary cleaning action.


The rollers should be installed in a way that the spiral moves the material towards the edge of the belt.

These rollers must not be employed as belt snub rollers.

The tables indicate the standard types and diameters with their dimensions according to European norms. On customer request cleaning rollers may be supplied with spirals in steel, with non standard dimensions and characteristics (for example steel spiral in flattened format).

#### Program

base roller type	Ø mm	standard design	spindle		bearing
			d	ch	
PSV/91-FHD	108	S	20	14	6204
	133	S			
PSV/92-FHD	133	S	25	18	6205
PSV/94-FHD	133	S	30	22	6206
RTL/1	60	NS	15	17	6202
	76	NS			
MPS/1	60	NS	15	17	6202
	76	NS			




# Ø 108 S 133 S

Base roller:

**PSV/91-FHD**  
D = 108, 133  
spindle 20  
bearing 6204  
ch = 14  
e = 4  
g = 9



**PSV/94-FHD**  
D = 133  
spindle 30  
bearing 6206  
ch = 22  
e = 4  
g = 12

**PSV/92-FHD**  
D = 133  
spindle 25  
bearing 6205  
ch = 18  
e = 4  
g = 12

belt	roller			weight	
	width mm	dimensions mm			Kg
arrangement 	arrangement			Ø 108	Ø 133
	B	C	A		
300	380	<b>388</b>	406	6.0	9.8
400	500	<b>508</b>	526	6.8	10.5
500	600	<b>608</b>	626	7.5	11.3
650	750	<b>758</b>	776	8.5	12.5
800	950	<b>958</b>	976	9.9	14.1
1000	1150	<b>1158</b>	1176	11.3	15.7

**Example of ordering**  
standard design  
PSV/91-FHD,20F,108S,758

for special designs  
see pages 80-81






## 2 Rollers

series

### Self cleaning



### 60 NS 76 NS


Base roller:


#### MPS/1

s = 3;  
spindle 15; d<sub>1</sub> = 20  
bearing 6202  
ch = 17

#### RTL/1

s = 2;  
spindle 15; d<sub>1</sub> = 20  
bearing 6202  
ch = 17

belt	roller D 60    Ø 76			weight Kg	
width mm	dimensions mm				
arrangement	B	C	A	RTL	MPS
					
300	380	388	406	2.5	32
400	500	508	526	3.3	4.1
500	600	608	626	3.9	4.8
650	750	758	776	4.8	5.9
800	950	958	976	6.0	7.4
1000	1150	1158	1176	7.2	8.9

belt	roller D 76    Ø 92			weight Kg	
width mm	dimensions mm				
arrangement	B	C	A	RTL	MPS
					
300	380	388	406	3.1	3.9
400	500	508	526	4.1	5.1
500	600	608	626	4.7	5.9
650	750	758	776	5.8	7.3
800	950	958	976	7.2	9.0
1000	1150	1158	1176	8.8	10.9

Example of ordering  
standard design  
MPS/1,15 B, 60 NS ,758

for special designs  
see pages 80-81